

# Multitask with perfection like a PRO!




Presenting  
TVS-E Touch POS  
**TP 415C PRO**




15 inch  
TFT Display with  
Capacitive Touch




Interface  
(6 Serial, 6 USB)



Stylish & Compact  
Design



Aluminum frame  
structure for  
optimizing the CPU  
heat dissipation



Intel® Celeron®  
Quad-core  
Processor J4125

System	Processor	Intel® Celeron™ Quad-Core J4125
	Chipset/BIOS	Intel® Gemini Lake SoC / AMI
	Storage	2.5" SSD 128GB
	Memory	4GB, DDR4 2400MHz x 1 Slot
		(Max 16GB, Optional)
	Graphics	Intel® UHD Graphics 600
	Expansion Slot	1 x m.2NVm2,
		1 x m.2 WiFi & Bluetooth(Optional)
Multi Monitor	3(# of Displays Supported)	
	- UP to 3 Monitors (Optional)	
Supported OS	Windows 10 Entry 64bit	
LCD Display	Type	15" LCD with WLED backlight
	Resolution	1024 x 768
	Touch	True-Flat Capacitive 10 Point Multi-Touch
I/O Interface	Serial	6(DB9 x 3, RJ50(RJ45) x 2, RJ11 x 1)
		COM1, 3, 5(DB9): +5V on Pin #9, Selectable by BIOS
		COM2, 4 (RJ50, RJ45): Support +5V and 12V for Special Devices and can be used for Kitchen Printer COM6(RJ11): USB 2.0 and RS232 with +5V/1A for Card Reader
	USB	4 x USB 3.0 (2 x Rear Top, 2 x Rear Bottom),
		3 x USB 2.0 (Rear Bottom x 2, RJ11 x 1)
	LPT(Parallel)	1(LPT / DB25 on Rear Bottom)
	Audio	1 x Audio-out / 3.5mm(Changeable for MIC)
	Display Port	1 x Display Port(Included 1 x USB 2.0 / Power Delivery +12V)
* Can be used for HDMI and DVI, VGA Monitor by Converter Cable		
LAN	1 x RJ45(Base-T 10/100/1000 Ethernet)	
Peripheral Options	2nd Display	9.7" Display
		1024 x 768
	Customer Display	VFD Type (Alphabet & Numeric, 20 Characters x 2 Lines)
	Card Reader (MSR/SCR)	Smart Card Reader: ISO/IEC7816 EMV Level 1 Magnetic Stripe Reader: ISO 7811 ID-1 All Tracks * Interface: USB(HID) and RS232C(COM6)
Dallas Reader	Dallas Reader(i-button): 6 Characters/Prefix and Suffix * Interface: USB(HID) and RS232C(COM6)	
Physical Dimension	Dimension(WDHmm)	362mm x 237mm x 336mm
	Weight	5.0Kg
Environment	Power Supply	DC 12V/5A (AC 100V~240V, 60W)
	Temperature	Operating: 0~50°C at 10% to 90% Humidity
	Certifications	CE, CB, FCC, KC

For trade enquiries contact

☎ 7550009339 / 9840460675 | ✉ sales-support@tvs-e.in

📘 /TVSElectronics 🌐 /tvs-electronics 📷 /tvselectronics