HS-2414W-3A

Specification	HS-2414W3A
Processor	Intel Bay Trail J1900 Quad Core CPU, up to 2.42 GHz, 2M Cache
System Memory	DDR3L SO-DIMM x 1, max. 8GB
Storage Device	SATA x 2 (one for HDD/SSD; the other for 1" SSD only]
Power Supply	24V/60W
Built-in Printer	3" detachable printer w/auto cutter, 250 mm/sec (max.)
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request
Display & Touch	
LCD	14" TFT LCD
Resolution	1366 x 768
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)
I/O & Expansion	
Serial Port	3, DB9 x 2 + RJ50 x 1, 5V/12V support on all COM ports
Parallel Port	Yes
Standard USB Port	4. USB 3.0 x 1+ USB 2.0 x 3
OTG USB	N/A
LAN Port	10/100 Mb x 1
Display Port	VGA x 1, 12V support for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable (printer driven)
PS/2 Port	Yes
Audio	Line-out x 1
Expansion Slot	Mini-PCle slot x 1
Physical Dimension	
Dimension (W x D x H in mm)	371.5 x 198 x 473
Weight (N. W. in kg)	5.8
Environmental	
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH
Built-in Options	
WiFi	Mini-PCle WiFi/BT module
MSR	3 tracks ISO or JISII (HID/VCOM selection)
Fingerprint Sensor	Optical type
RFID Reader	Support MIFARE Ultralight and Classic 1K card (HID/VCOM Selectable)
Scanner	2D barcode scanner
iButton	Yes (cannot coexist with Fingerprint Sensor)
4G / LTE Communication	Single SIM slot, selected band support
Attachment Options	
POS Monitor	Non-touch TFT LCD: 7"/9.7"/12.1"; PCAP touch TFT LCD: 9.7"
Line Display	2 x 20 rear-mount VFD customer line display; 2 x 20 rear-mount LCD customer line display; 7" color LCD graphical line display

Taking Space Saving to Extremes

HS-2414W-3A

Space Saving All-in-one POS Terminal

* Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

* The product information and specifications are subject to change without prior notice. * Please refer to the website for more attachment options.

EC

POSIFLE

Certification

POSIFLEX TECHNOLOGY (INDIA) PVT. LTD.

RoHS

#7/3, 3rd Floor, Jeet Dynasty, Swamy Vivekananda Rd, Nagavarapalya, Bengaluru, Karnataka 560093 Tel : +91 80 4078 2700 | Mob : +91 9535432110 Email : marketing@posiflexindia.com | www.posiflexindia.com

8 Authorized Distributor / Reseller

Winde Embe





HS-2414W-3A

The HS-2414W-3A is a whole new generation of high-end all-in-one POS terminal, packing innovativeness and functionality in compact design with stylish look. It is the perfect fit for retail businesses where space is at premium.





Innovative All-in-one Terminal

This compact all-in-one 10"/12"/14" touch POS now comes with a detachable receipt printer for easy maintenance. Add an optional 2D barcode scanner while the printer is on board, making the HS-3500 Series the most well-rounded all-in-one POS terminal in the market.

Integrated Design with Advanced Manageability

The HS-3500 Series integrates the most widely used peripherals including 3" thermal printer, MSR, fingerprint sensor, 2D barcode scanner and 2ndcustomer display to support your daily POS operation. The detachable modularized design allows quick access to the components, enabling fast and easy service and upgrades.



Detachable Receipt Printer -

Aesthetics

Dressed from head to toe in timeless black or white color, the only trend that never goes out of style, and with stylish touches added throughout, the HS-3500 Series is not just a piece of machinery, it is an elegantly crafted piece of art that looks right at home in any store decoration.



2D Barcode Scanner





Optional Built-in MSR Fingerprint Sensor and RFID Reader