



BP-02

Portable Bluetooth Printer

- 2" Bluetooth Printer
- Mini size, Lightweight , Durable performance
- Quick charge with Rechargeable Li-ion Battery
- Dual Connectivity for fast and easy data transfer
- Direct Thermal Receipt Printer



Windows



Android



Linux

Specification

Print Way	Thermal sensitive line dot method
Print Head life	50km
Paper Width	56mm
Printing thickness	60 ~ 80µm
Valid printing width	48mm
Resolution	8 dot/mm(230 dpi)
Dot/Line	384 dots
Printing Speed	60-80 mm/s
Printing content	Support any language
Outer dimension	103 x 75 x 46 mm
Weight	340g
Rolling paper Diameter	≤30.5mm
Interface	Original IR(RAW_IR), VIR, IrDA (IrCOMM) RS232 port, Bluetooth 2.0 , USB interfaces varied between different models.
Environment Parameters	Working temperature: -10°C ~ 50°C Working humidity: 20% ~ 85% Storing temperature : -20°C ~ 70°C Storing humidity: 5% ~ 95%
Paper feeding method	Easy paper loading
Mark position	detecting mark position
Paper sensor	An LED indicator flashes when the paper runs out/Cover open, and an alarm sounds.
Printing Command	ESC/POS compatible with commands set
Backup	Rechargeable li-ion battery upto 9 hrs backup
Power alarm	When the battery is low, the indicator flashes and the printer gives two short hoots. The buzzer will also sound repeatedly to indicate charging time.
Power Input	Input 240V AC
Barcode Symbolologies	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Aztec, Data Matrix, GS1 Databar, MaxiCode, PDF417, QR code
Cutting method	Manual